

WX802/OB

Outdoor Wall Speaker

AUDAC

► Features

- Outdoor 2-Way wall speaker
- Clear and powerful sound reproduction
- 5-pole waterproof connector
- Electroplated steel mounting brackets
- Rotatable power tapping connector (IP55)
- Vertical or horizontal mounting
- Aluminium grill

► Applications

- Wide variation of outdoor applications
- Terrace, Patio
- Amusement parks
- Playgrounds
- Sports fields
- Gardens



The AUDAC WX802/OB is a powerful 2-Way, 8" loudspeaker cabinet which is specifically designed for outdoor use. It lends itself to a wide variation of outdoor applications, ensuring a clear and powerful sound reproduction.

Hereby, the WX802/OB is the perfect companion for outdoor applications where a clear background music is desirable throughout the day, and a more powerful sound with deeper bass is necessary when the party erupts after sunset.

The sound is coming from a weather-proof treated 8" low frequency loudspeaker in combination with a 1" dome tweeter, which are built in a aesthetical and solid synthetic enclosure.

The mounting of the loudspeaker can be done in a horizontal and vertical way by means of the included mounting bracket, which passes the 96 hours salt-spray test due to its special electroplated coating.

A drain hole behind the aluminium front grill allows to let the moisture flow out, when condensation occurs.

The connections and power settings can be made with the rotatable waterproof connector on the rear side of the loudspeaker. The power can be set in three adjustable steps for 100V and one step for 16 Ohm standard low impedance applications.

- 60 Watt, 30 Watt, 15 Watt @ 100V
- 70 Watt @ 16 Ohm

► Specifications

SYSTEM SPECIFICATIONS	
Max. power	140 W
RMS power	70 W
Line Transformer Power Tap 1	60 W / 167 Ohm
Line Transformer Power Tap 2	30 W / 333 Ohm
Line Transformer Power Tap 3	15 W / 667 Ohm
Frequency Response -3dB	60 Hz - 17 KHz
Frequency Range -10dB	50 Hz - 20 KHz
Crossover frequency	2.4 KHz
Sensitivity 1W / 1m	89 dB
SPL max W / 1m @ 8 Ohm	108 dB
SPL max W / 1m @ 100 Volt	106 dB
Impedance	16 Ohm
Crossover	Passive built-in
Horizontal coverage	110°
Vertical coverage	110°
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	270 x 360 x 215 mm
Weight net	7.5 Kg
Drivers	HF 1" LF 8"
Construction	ABS housing
Mounting	Mounting bracket
Front finish	Aluminium grill
Connectors	5-pin waterproof connector
Colour	Black (RAL 9005)
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume (2pcs)	15 Kg - 0.0636 Cbm
Accessory included	Mounting bracket 5-pin connection cable (30 cm)
Optional accessories	AU570120005 - 5-pin cable 0.5 m AU570120025 - 5-pin cable 2.5 m AU570120050 - 5-pin cable 5 m
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our product	