


BLC 550 T

ABS SURFACE MOUNTING WALL LOUDSPEAKERS



DNH ABS surface mounting wall or ceiling loudspeaker


- Power 6 Watt
- 100V transformer
- SPL 1W/1m 90dB
- Dispersion (-6dB) 1kHz/4kHz 170°/50°
- White RAL9010 colour



	BLC 550 T
Code	09355
Features	Loudspeaker with transformer
Mounting system	Screw terminals
Rated/Maximum power	6/15W RMS
Colour	White
Frequency response	150÷15.000Hz
Sensitivity 1W/1m	90dB
Maximum SPL 1m	97dB
Weight	1,2 Kg
Dimensions	∅ 206x66mm

SAFE 10 PT

ABS SURFACE MOUNTING WALL LOUDSPEAKER



DNH surface mounting self-extinguishing polycarbonate wall loudspeaker

- Power 6 Watt
- 100V transformer
- SPL 1W/1m 85dB
- Dispersion (-6dB) 1kHz/4kHz 140°/100°
- Grey RAL7035 colour



	SAFE 10 PT
Code	09356
Features	IP56 weatherproof and V0 self-extinguishing, with transformer
Mounting system	Screw terminals
Rated/Maximum power	10/15W RMS
Colour	Grey
Frequency response	150÷20.000Hz
Sensitivity 1W/1m	85dB
Maximum SPL 1m	95dB
Weight	0,8 Kg
Dimensions (WxHxD)	206x55x104mm