

Loudspeaker cabinets

- Extremely light and sturdy enclosure made of gas injection moulded polypropylene, black (STUDIO.PRO 9B) or RAL 7035 grey colour (STUDIO.PRO 9W), stand adapter, 2 M6 anchoring points
- 2-way bass-reflex system with 130mm woofer and 25mm high frequency tweeter
- Power 120 Watt
- Frequency response 80Hz-20 kHz
- Sensitivity 95.5dB 1W/1m Maximum SPL 116.5dB
- Dispersion (HxV) 90°x60°
- SUB-D input connectors

Speaker cabinets

Same characteristics as the STUDIO.PRO 9B/W models except for the following:

- Power 80W
- 70-100V 4-position line transformers: 5W/20W/45W/80W
- Sensitivity 95.5dB 1W/1m Maximum SPL 114.5dB

Loudspeaker cabinet

Same characteristics as the STUDIO.PRO 9B/W models except for the following:

- 80W RMS internal amplifiers for the woofer and 20W RMS for the driver
- ADAP® (Advanced Dynamic Active Protection) designed to limit amplifier saturation and ensure complete reliability of the system even in extreme conditions; 24dB/oct active filters
- Frequency response 70Hz-20 kHz
- Sensitivity 95dB 1W/1m
- Maximum SPL 115dB
- Control panel with Ground Lift, Combo XLR/JACK inputs, XLR male output, limiter, volume control

**SJ 9 B/W** Adjustable wall support

Model	Code	Colour
SJ 9 B	19706	black
SJ 9 W	19705	RAL 7035 grey

SJ 9 UB/UW Wall mounting brackets

Model	Code	Colour
SJ 9 UB	19708	black
SJ 9 UW	19707	RAL 7035 grey

ST 20 B Adjustable floor stand

Code 19710
Adjustable metal floor stand, with safety locking device, max weigh 55 kg

	STUDIO.PRO 9 B/W	STUDIO.PRO 9 BT/WT	STUDIO.PRO 9 BA
Code	19678 / 19677	19680 / 19679	19681
Colour	black - RAL 7035 grey	black - RAL 7035 grey	black
Configuration	2 way	2 way	2 way
Recommended amplifier	120W rms	80W rms	-
Internal amplifier	-	-	80W + 20W
Long term power (AES)	60W	-	-
Short term power (IEC 268-5)	240W	-	-
Nominal impedance	8ohm	-	-
Line transformer	-	70V-100V	-
Frequency response (@-6dB)	80Hz - 20kHz	80Hz - 20kHz	70Hz - 20kHz
Low frequency woofer	1x200 ø 38 mm coil	1x200 ø 38 mm coil	1x200 ø 38 mm coil
High frequency woofer	1xTweeter+horn ø 20 mm coil	1xTweeter+horn ø 20 mm coil	1xTweeter+horn ø 20 mm coil
Sensitivity 1W/1m	95,5dB	95,5dB	95dB
Max. SPL 1m	116,5dB	114,5dB	115dB
Dispersion	90°x60° HxV	90°x60° HxV	90°x60° HxV
Crossover frequency	3,5 kHz	3,5 kHz	2,5 kHz
Recommended hp filter	60Hz 24dB oct	60Hz 24dB oct	-
Input connectors	spring terminals	spring terminals	Combo XLR-M/JACK
Weight	4,8 kg	4,8 kg	5,4 Kg
Dimensions (WxHxD)	255x415x245mm	255x415x245mm	255x415x245mm

Loudspeaker cabinet

- Extremely light and sturdy enclosure made of gas injection moulded polypropylene, black colour, integral handle
- Stand adapter, 2 M6 anchoring points


- 2-way bass-reflex system with 320mm woofer and 25mm high frequency tweeter
- Built-in class G amplifiers 150W RMS for the woofer and 50W RMS for the high frequency unit; ADAP (Advance Dynamic Active

Protection) designed to limit amplifier saturation and ensure complete reliability of the system even in extreme conditions (STUDIO.PRO 14BA)


- 24dB/oct active filters (STUDIO.PRO 14BA)
- Power 250 Watt
- Impedance 8 Ohm
- Frequency response 60Hz-20 kHz
- Sensitivity 98dB 1W/1m
- Maximum SPL 122/125dB (STUDIO.PRO 14B) 121dB (STUDIO.PRO 14BA)
- Dispersion (HxV) 90°x60°
- 2 speakon input connectors
- Control panel with Ground Lift switch, Combo XLR/JACK inputs, XLR male output, limiter, volume control (STUDIO.PRO 14BA)

**SJ 14 UB****Wall mounting brackets**

Model	Code	Colour
SJ 14 UB	19709	black

ST 30 B**Adjustable floor stand****Code 18239**

Adjustable, aluminium floor stand, with safety locking device

ST 40 B**Adjustable floor stand****Code 18240**

Adjustable, metal floor stand, with safety locking device

	STUDIO.PRO 14B	STUDIO.PRO 14BA
Code	19682	19683
Configuration	2 way	2 way
Recommended amplifier	250W rms	-
Internal amplifier	-	150W+50W rms
Long term power (AES)	125W	-
Short term power (IEC 268-5)	500W	-
Nominal impedance	8ohm	-
Frequency response (@-6dB)	60Hz - 20kHz	60Hz - 20kHz
Low frequency woofer	1x320 ø 51 mm coil	1x320 ø 51 mm coil
High frequency woofer	1x25.4+horn ø 25.4 mm coil	1x25.4+horn ø 25.4 mm coil
Sensitivity 1W/1m	98dB	98dB
Maximum SPL 1m	122/125dB	121dB
Dispersion	90°x60° HxV	90°x60° HxV
Crossover frequency	2,5 kHz	2 kHz
Recommended hp filter	40Hz 24dB oct	40Hz 24dB oct
Input connectors	2xspeakon	Combo XLR/JACK
Weight	13,5 kg	16 kg
Dimensions (WxHxD)	410x663x387mm	410x663x387mm