

PH 10 T

ABS HORN LOUDSPEAKERS

PH 20 T

PH 30 T

ABS HORN LOUDSPEAKERS

IP 66 weatherproof circular horn loudspeaker in ABS






- RAL 7035 light grey colour
- Stainless steel U bracket
- Power 10/5/2,5/1,25 Watt
- 100V transformer
- Max/min operating temperature 85 C°/-20°C
- SPL 1W/1m 106dB
- Dispersion (-10dB) 1kHz/4kHz 180°/70°

IP 66 weatherproof circular horn loudspeaker in ABS

- RAL 7035 light grey colour
- Stainless steel U bracket
- Power 10/5/2,5/2.5 Watt
- 100V transformer
- Max/min operating temperature 85 C°/-20°C
- SPL 1W/1m 108dB
- Dispersion (-10dB) 1kHz/4kHz 180°/60°

IP 66 weatherproof circular horn loudspeaker in ABS

- RAL 7035 light grey colour
- Stainless steel U bracket
- Power 30/15/7.5/3.75 Watt
- 100V transformer
- SPL 1W/1m 110dB
- Dispersion (-10dB) 1kHz/4kHz 180°/60°



	PH 10 T	PH 20 T
Code	11474	11475
Features	Plastic, weatherproof and UV protection with transformer	Plastic, weatherproof and UV protection with transformer
Mounting system	U Bracket	U Bracket
Rated/Maximum power	10 Watt	20 Watt
Colour	Light Grey RAL 7035	Light Grey RAL 7035
Frequency response	400-8.000 KHz	350-8.000 KHz
Sensitivity 1W/1m	106dB	108dB
Maximum SPL 1m	116dB	121dB
Input voltage	100/70 Volt	100/70 Volt
Operating temperature	da -20°C a 85°C	da -20°C a 85°C
Weight	1,3 Kg	1,9 Kg
Dimensions	ø 138x200mm	ø 203x254mm

	PH 30 T
Code	10446
Features	Plastic, weatherproof and UV protection with transformer
Mounting system	U Bracket
Rated/Maximum power	30 Watt
Colour	Light Grey RAL 7035
Frequency response	330-8.000 KHz
Sensitivity 1W/1m	110dB
Maximum SPL 1m	124dB
Input voltage	100/70 Volt
Operating temperature	da -20°C a 85°C
Weight	2,1 Kg
Dimensions	ø 238x287mm